

## VRIEZER ADVANCE F 70-3 L DR

Product Serie: Advance

Artikelnummer: 123701010

Hoshizaki ADVANCE is a series of durable refrigeration and freezer cabinets, exceeding the requirements of demanding commercial kitchen environments.

The Advance F 70-3 L DR is a Freezer with a net internal volume of 420 liters. The outside dimensions are 654 x 830 x 1980-2030 mm.

### DURABLE MATERIALS

The interior and exterior are made of stainless steel, the best material for humid locations. ADVANCE cabinets are designed to withstand the demanding conditions of large kitchen operations.

### MAXIMUM STORAGE SPACE

With shelves all the way from the top to the bottom of the cabinet, the inside space can be efficiently utilized for maximum produce storage.

### HYGIENE AND FOOD SAFETY

Thanks to the rounded corners and seamless surfaces, frequented cleaning routines become a quick and simple task. The practical anti-tipping shelves prevent spillage. The cabinet has a rounded base and comes with removable gaskets for easy wiping.

### MONO-BLOCK DESIGN

The ADVANCE refrigeration system uses a mono-block construction. This brings two important advantages. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage. Additionally, it is removable for easier maintenance and repair.

### UNIFORM KITCHEN DESIGN

The exterior of all ADVANCE cabinets features a uniform design that fits seamlessly into your Hoshizaki kitchen concept.

### TEMPERATURE STABILITY

The intelligent air distribution system allows high performance, ensuring temperature stability despite frequent door openings and during defrosting.



## SPECIFICATIES

<b>Productnaam</b>	Vriezer	<b>Energie verbruik (kWh/Jaar)</b>	2.171
<b>Temperatuurbereik</b>	-25/-12°C	<b>Standaard energie Efficiëntieklaasse</b>	ISO 22041-2019
<b>Inhoud, bruto (liter)</b>	600	<b>Energie Efficiëntieklaasse</b>	D
<b>Netto bruikbaar volume (liter)</b>	420	<b>Energie Efficiëntie Index EEI</b>	61,31
<b>Uitwendig</b>	RvS AISI 304	<b>Geluidsniveau dB(A)</b>	54
<b>Inwendig</b>	RvS AISI 304	<b>Klimaatklasse</b>	5
<b>Afmetingen B x D x H (mm)</b>	654 x 830 x 1980-2030	<b>Poten / Wielen</b>	H = 130/180 mm (L)
<b>Gewicht, verpakt (kg)</b>	133	<b>Koelmiddel (kg)</b>	0,082
<b>Isolatie (mm)</b>	60 (polyurethaan)	<b>CO2 Equivalent (kg)</b>	0,246
<b>Koelmiddel</b>	R290	<b>GN – Afmetingen rooster</b>	2/1 GN diep
<b>GWP</b>	3	<b>Maximaal aantal roosters</b>	22
<b>Koelcapaciteit bij -25°C (Watt)</b>	506	<b>Aantal roosters</b>	4
<b>Aansluiting</b>	230V, 50 Hz	<b>Uitgerust met</b>	Rechtsdraaiende omkeerbare deur met slot, automatische deursluiting, 4 grijze roosters, LED-verlichting
<b>Aansluitwaarde (Watt)</b>	650	<b>Deur type</b>	Geïsoleerde deur