

## Technical information

# Aura 42XL/42XL+



### Characteristics

- With one sealing bar as standard (front)
- With double seal as standard (two sealing wires)
- Optional at no extra cost: Cut-off/wide seal
- Pump maintenance and cleaning program
- Standard Liquid control
- I-Vac: Intelligent vacuum-packing with advanced software
  - easy product selection
  - fast access of frequently used functions and programmes
- Standard soft air
- Stainless steel casing and transparent lid
- Supplied with three insert plates for a faster cycle and good positioning

### Options

- Gas Flush / MAP packaging
- 2 seal bars (front - back)

### Accessories

- Inclined insert plate (for packing liquids)
- Thermal laser printer
- External adapter
- Maintenance set for standard maintenance
- Trolley with shelves



Specs	Aura 42XL	Aura 42XL+
Chamber LxWxH (mm)	460x420x180	460x420x180
Machine LxWxH (mm)	613x491x469	613x491x469
Voltage	230V-1-50Hz 100V-1-50/60Hz 110/115V-1-60Hz 220V-1-60Hz	
Pump capacity 50 Hz/60 Hz (m3)	16 / 19	21 / 25
Machine cycle 50 Hz/60 Hz (sec.)	14-45 / 12-40	13-35 / 11 - 31
Power (kW)	0,6 - 1,0	0,8 - 1,0
Weight (kg)	68	72
Net seal length (mm)	410	410
Sealing bar configuration -standard - option	standard 	option 

### Dimensions mm

